

Patent Abstracts of Japan

PUBLICATION NUMBER : 09275021
PUBLICATION DATE : 21-10-97


APPLICATION DATE : 04-04-96
APPLICATION NUMBER : 08082770

APPLICANT : NKK CORP;

INVENTOR : NAMIKAWA MISAO;

INT.CL. : H01F 27/245 C22C 38/00 C22C 38/02
H01F 1/16 H01F 27/33

TITLE : LOW NOISE IRON CORE EXCELLENT
IN MAGNETIC CHARACTERISTIC



ABSTRACT : PROBLEM TO BE SOLVED: To provide a low noise iron core having an excellent core loss characteristic, low-noise as well, excellent in mass-producibility and producible at a low cost, and having an excellent magnetic characteristic by using non-oriented silicon steel strips having a specific absolute value of DC magnetostriction, and laminating them.

SOLUTION: An iron core A is composed of a laminated iron core formed by laminating a plurality of non-oriented silicon steel strips 1 punched into the shape of a cut core. Accordingly, noise is generated less compared with a wound iron core, since no resonance is generated. Besides, the Si content of the non-oriented silicon steel strips 1 is in a range of 4-7wt.%, to make the absolute value of the DC magnetostriction of the non-oriented silicon steel strips 1 to be used 1.5×10^{-6} or less. Consequently, it becomes possible to obtain a low noise iron core having an excellent soft magnetic characteristic. Since it is a cut core type laminated iron core by the use of non-oriented silicon steel strips 1 having an absolute value of DC magnetostriction of 1.5×10^{-6} or less, in this way, it becomes possible to make the best use of both the merit of the non-oriented silicon steel strips 1 and that of the laminated iron core.

COPYRIGHT: (C)1997,JPO